


Features

- ✓ Rated power 8kW 9kW
- ✓ Rated voltage from 40V to 800V
- ✓ Rated current 225A to 10A
- ✓ **Other output ratings can be customized**
- ✓ 3U rack mount cabinet design
- ✓ 4 digits LED display for voltage and current
- ✓ Low ripple, high stability
- ✓ List mode function, Auto Run function, Remote sensing function
- ✓ **No overshoot during startup**
- ✓ **Soft start by hardware, and adjustable voltage rise time by software**
- ✓ Remote ON/OFF control
- ✓ Preset function, setting of voltage and current with output open circuit
- ✓ Multiple protections: OVP, OTP, ACF and current limit protections
- ✓ Standard interface: RS232 & RS485, support ModBus-RTU commands
- ✓ Optional interface: DC 0-5V, 0-10V or 4-20mA analog interface for control and feedback; **LAN interface**

High Power DC Power Supply



Product Photos (3U frame for 6kW~9kW)



TWINTEX • www.twintex.com.tw

Taipei, Taiwan: Tel: +886-02-2915 0101 • Fax: +886-02-2916 0101
Shenzhen, China: Tel.: +86-755-2812 9890 • Fax: +86-755-2814 9802

High Power DC Power Supply

Model	Rated Output				Model	Rated Output		
	V	A	W			V	A	W
PCL8000-40	0~40V	0~200A	8kW		PCL9000-40	0~40V	0~225A	9kW
PCL8000-50	0~50V	0~160A	8kW		PCL9000-60	0~60V	0~150A	9kW
PCL8000-60	0~60V	0~133A	8kW		PCL9000-90	0~90V	0~100A	9kW
PCL8000-1H	0~100V	0~80A	8kW		PCL9000-1H	0~100V	0~90A	9kW
PCL8000-150	0~150V	0~53A	8kW		PCL9000-120	0~120V	0~75A	9kW
PCL8000-2H	0~200V	0~40A	8kW		PCL9000-150	0~150V	0~60A	9kW
PCL8000-3H	0~300V	0~26.7A	8kW		PCL9000-2H	0~200V	0~45A	9kW
PCL8000-4H	0~400V	0~20A	8kW		PCL9000-3H	0~300V	0~30A	9kW
PCL8000-5H	0~500V	0~16A	8kW		PCL9000-4H	0~400V	0~22.5A	9kW
PCL8000-6H	0~600V	0~13.3A	8kW		PCL9000-5H	0~500V	0~18A	9kW
PCL8000-8H	0~800V	0~10A	8kW		PCL9000-6H	0~600V	0~15A	9kW
Weight	20~25kg							
Dimensions	600Wx734.6Hx732D mm (including wheels)							
AC Input	3φ4W (L1, L2, L3, PE), 380V±10% 47~63Hz							